



Claim 4 (currently amended): The tube as recited in claim 1 wherein the beam-splitting device includes a Bauernfeind prism configured to reflect therein twice the light second partial beam coming from the adaptation interface.

Claim 5 (original): The tube as recited in claim 4 wherein the beam deflecting device includes a deflecting prism configured to deflect by 90 degrees the light beam coming from the adaptation interface, and wherein the Bauernfeind prism is disposed between the deflecting prism and the beam deflecting unit.

Claim 6 (currently amended): The tube as recited in claim 5 wherein the beam-splitting device includes an optical component associated with the Bauernfeind prism, the optical component being configured to split off, ~~to at least one of a documentation interface and a detector, at least a part of the light beam coming from the adaptation interface~~ the light beam coming from the adaptation interface into the first and second partial beams.

Claim 7 (original): The tube as recited in claim 6 wherein the optical component includes a prism attached to the Bauernfeind prism.

Claim 8 (previously presented): The tube as recited in claim 7 wherein the prism is cemented to the Bauernfeind prism.

{W:\20793\0204560\us0\00883404.DOC UNRECORDED\UNRECORDED\UNRECORDED\UNRECORDED\UNRECORDED }

Claim 9 (currently amended): The tube as recited in claim 1 wherein optical properties of the beam deflecting device are selectable so that a length of ~~an~~ a respective optical path of ~~the light beam at least one of the first and second partial beams~~ in the tube is adaptable.

Claim 10 (original): The tube as recited in claim 1 wherein at least a portion of the beam splitter device is movable into and out of a working position.

Claim 11 (original): The tube as recited in claim 10 wherein the at least a portion of the beam splitter device is movable into and out of the working position guided by a magazine slider.

Claim 12 (original): The tube as recited in claim 1 wherein the operator interface and the beam deflecting unit are rotatable about a rotation axis, the rotation axis being perpendicular to an optical axis of the light beam.

Claim 13 (original): The tube as recited in claim 1 wherein, upon a rotation of the operator interface through a first angle, the beam deflecting unit is configured to rotate through a second angle half as large as the first angle.

Claim 14 (original): The tube as recited in claim 1 further comprising a lens device disposed between the adaptation interface and the beam deflecting device, the lens device having a positive refractive power.

Claim 15 (original): The tube as recited in claim 14 wherein the lens device is configured to convert a substantially collimated light beam into a converging light beam.

{W:\20793\0204560\us\00883404.DOC 000000000000000000000000 }

Claim 16 (original): The tube as recited in claim 1 further comprising a lens device rotatably disposed between the beam deflecting unit and the operator interface, the lens device including a first lens having a negative refractive power and a second lens having a positive refractive power.

Claim 17 (original): The tube as recited in claim 16 wherein the first lens is configured to substantially collimate a light beam coming from the beam deflecting device.

Claim 18 (original): The tube as recited in claim 17 further comprising a telescopable assembly telescopable in a direction of an optical axis of a light beam extending therein, the second lens and the operator interface being included in the telescopable assembly.

Claim 19 (original): The tube as recited in claim 1 wherein the operator interface includes a binocular element configured for eyepiece viewing by an operator.

Claim 20 (currently amended): The tube as recited in claim 1 wherein the beam-splitting device is configured to split off, the first partial beam to at least one of a documentation interface and a detector, ~~at least a part of the light beam coming from the adaptation interface.~~

Claim 21 (currently amended): The tube as recited in claim 20 wherein the beam-splitting device includes a Bauernfeind prism configured to reflect therein twice the second partial beam, and includes an optical component associated with the Bauernfeind prism, the optical component being configured to split off; the first partial beam to at least one of the documentation interface and the detector, the at least a part of the light beam coming from the adaptation interface.

Claim 22 (previously presented): The tube as recited in claim 21 wherein the optical component includes a prism attached to the Bauernfeind prism.

Claim 23 (previously presented): The tube as recited in claim 22 wherein the prism is cemented to the Bauernfeind prism.

{W:\20793\0204560us0\00883404.DOC MICROPHOTOCOPYING\2\1004560 }